

EP3800 SLIDING TABLE PANEL SAW



DESCRIPTION

An all-rounder work center suitable for milling, routing, drilling, side milling, sawing and other applications. Ideal for panel furniture, solid wood furniture, office furniture, wooden door productions, as well as other non-metal and soft metal applications. The double work zones guarantee non-stop work cycle where an operator can load and unload workpieces on one zone without interrupting the machine operation on the other. It features world class components from Italy and Germany with strict machining procedures.

KEY FEATURES


- Sliding Carriage: maximum cut quality guaranteed over time
- Operator's Support: one cut only, the correct one
- Saw Unit: a perfect cut

STANDARD CONFIGURATIONS

Model	EP3800
Max cutting height at 90° (mm)	95mm with blade 315mm
Max cutting height at 45° (mm)	67mm with blade 315mm
Scoring saw Diameter	120mm
Blade tilt (degrees)	45
Blades lifting and tilt	Electronic
Control and working height readout	Motion 1
Main blade rotating speed (rpm)	4500rpm
Scoring unit rotating speed (rpm)	8000
Saw unit motor power (S1) kW (HP)	5.5 (7,5) Hz50
Scoring unit motor power (S1) kW (HP)	1,3 (1,7) Hz50
Squaring capacity 3800 carriage	3800x3200 mm
Cutting width on parallel fence	1250mm
Exhaust outlet diameter at the base (mm):	120
Exhaust outlet diameter on overhead protection (mm):	80

KEY FEATURES

EP3800 SLIDING TABLE PANEL SAW



Saw Unit with a max cutting height of 95 mm. The cast iron saw unit with a rigid closed loop structure can accommodate a blade up to 315 mm diameter with the scoring blade mounted.

Mounted scoring blade ensures perfect and easy cutting of veneer panels and thick solid wood material. The saw blade uses 100% of the motor power, thanks to the scoring blade with an independent motor as standard.




Upper mobile control panel with "EASY" electronic control with 7" LCD display. Electronic positioning of the vertical positioning and tilting of tool. Electronic positioning of the parallel fence positions.


Electronic positioning of the parallel fence positions. Operator's help function for the carrying out of complex cutting. Optional management of tools database Optional



Powered parallel fence controlled by NC Position reading by means of encoder Sliding on linear fence with recirculating ball bushing through recirculating ball screws




Continuous adjustment by means of pushbutton or automatic positioning Possibility of incremental positioning Automatic set up Total exclusion of fence under the worktable. Cutting width 1250mm



Polished steel roller for large panels



Fence for angular cutting Squaring fence for angular cuts.



Sliding Table - Anodized aluminium alloy sliding carriage on high precision sub rollers hardened steel guides. This table is the exact copy of the most famous German brand panel saw in the world. Sliding table length: 2600mm



Squaring fence with no. 3 LCD readouts for stops position. Stop is equipped with electronic digital readout with detecting system on magnetic band and readout on LCD display



Safety Protections
Emergency push button located on the front machine side.
Emergency push buttons located on parallel fence side.
Blade access door with quick locking and safety microswitch.



Safety Protections
Overload protection.
Overhead saw guard.
Certificate of conformity with "C.E. Standards".