

**Excitech Australia Pty Ltd**  
ABN 38 665 472 123

Date:28-08-2025

30/10 Yato rd,  
Prestons 2170

M: 0424 362 088

E: service@excitechaustralia.au

**Attn: Test Excitech**

**RE:** <'MODEL NUMBER'>

Thank you for your recent inquiry regarding Excitech Australia's <'MODEL NUMER'>.

**EXCITECH: LEADING THE WAY WITH CONTINUOUS INNOVATION AND EXCELLENCE**

Since 2006, Excitech has become a leading name in machinery manufacturing. With facilities in Shandong and Guangdong, China, we are committed to delivering topquality products that meet the highest standards. This dedication has helped us achieve significant milestones and stay competitive in a fast-changing market.

We understand that choosing the right machinery is a significant investment. Therefore, we are committed to creating unending value for our customers and ensuring that they receive the best possible service.

Please find enclosed a formal proposal for the supply and installation of the <'MODEL number'>.

Should you require further information, please do not hesitate to contact me at **0424 362 088** or email me at [jose@excitechaustralia.au](mailto:jose@excitechaustralia.au).

Your faithfully,

**Jose Ojeda**  
Managing Director

## EF463S AUTOMATIC EDGE BANDER



### DESCRIPTION

With room to grow, this mid-level edgebender allows an entry level business to upscale, yet an established business keep up to demand. Specifications of this model include spray release agent, pre-milling, gluing, end trimming, fine radius trimming, twin motor corner rounding, radius scraping, flat scraping and off cut, spray cleaning agent, buffing and hinge protection.


### KEY FEATURES

- Tape total meter calculation function within a period (like one day, one week or one month)
- Workpiece quantity calculation function within a period (like one day, one week or one month)
- Machine running time calculation function within a period (like one day, one week or one month)
- Workpiece thickness auto measurement, if panel thickness is over setting thickness, it pauses automatically
- Add air blow device, ensuring clean workpiece; end trimming and scraping equip with dust collecting device

## STANDARD CONFIGURATIONS

Model	EF463S
Workpiece length	Min 150 mm
Workpiece width	Min 80 mm
Workpiece thickness	10-60 mm
Edge thickness	0.4-3 mm
Edge width	12-65 mm
Feed speed	16-20 m/min
Net Weight	2205 kg
Input voltage	415 V
Input frequency	50 HZ
Output frequency	200 HZ
Total power	15.7 KW
Machine dimension	6280*850*1550 mm
Packing size	6380*1050*1720 mm

## KEY FEATURES EF463S AUTOMATIC EDGE BANDER




**Gluing Unit and Heating Lamp**  
High precision glue roller ensures perfect gluing on various materials. Temperature is controlled by a meter heat preservation can be set.



Automatic lubrication system, make the maintenance easy.




Delta Touch Screen



Off-cut by removing the PVC chips which left on the parts during the Radius scraping, which can avoid the chips winding on the buffing motors.




Heat Lamp takes the chill out the board to pre heat the board so glue does not set too quickly.



Flat Scraping  
Remove the extra glue which may be left on the panel top and bottom.



Fine Trimming & Scraping Unit  
Two motors traveling on linear guides for end trimming.




Hinge Kit Protection



End Trimming & reciprocating cloth wheels make clean and high gloss buffing. Spray cleaning agent for perfect polishing.



Gravity Fed Top Glue Pot  
Teflon Coated (nonstick)  
Easy Cleaning  
Makes colour changes easy  
EVA to PUR Glues



Edge Press by Rollers  
One big precision roller and 3 small to make sure the edge is pressed seamlessly to the workpiece. All rollers have their independent pressure control valve. The latter further ensures that the edge is properly pressed to the workpiece

## KEY FEATURES

### EF463S AUTOMATIC EDGE BANDER



Spray release agent & Pre-milling Unit Equipped with diamond tools for better cut and longer use.  
This device removes the burr or unevenness on the edge of the workpiece, leaving a smooth surface for the edge banding.  
Spray release agent for perfect pre-milling



Corner Rounding/trimming  
With 2 motors, this device works well with various edge thicknesses and invariably result in perfect round corner.

## EF463S AUTOMATIC EDGE BANDER



### DESCRIPTION

With room to grow, this mid-level edgebender allows an entry level business to upscale, yet an established business keep up to demand. Specifications of this model include spray release agent, pre-milling, gluing, end trimming, fine radius trimming, twin motor corner rounding, radius scraping, flat scraping and off cut, spray cleaning agent, buffing and hinge protection.


### KEY FEATURES

- Tape total meter calculation function within a period (like one day, one week or one month)
- Workpiece quantity calculation function within a period (like one day, one week or one month)
- Machine running time calculation function within a period (like one day, one week or one month)
- Workpiece thickness auto measurement, if panel thickness is over setting thickness, it pauses automatically
- Add air blow device, ensuring clean workpiece; end trimming and scraping equip with dust collecting device

## STANDARD CONFIGURATIONS

Model	EF463S
Workpiece length	Min 150 mm
Workpiece width	Min 80 mm
Workpiece thickness	10-60 mm
Edge thickness	0.4-3 mm
Edge width	12-65 mm
Feed speed	16-20 m/min
Net Weight	2205 kg
Input voltage	415 V
Input frequency	50 HZ
Output frequency	200 HZ
Total power	15.7 KW
Machine dimension	6280*850*1550 mm
Packing size	6380*1050*1720 mm

## KEY FEATURES EF463S AUTOMATIC EDGE BANDER




**Gluing Unit and Heating Lamp**  
High precision glue roller ensures perfect gluing on various materials. Temperature is controlled by a meter heat preservation can be set.



Automatic lubrication system, make the maintenance easy.




Delta Touch Screen



Off-cut by removing the PVC chips which left on the parts during the Radius scraping, which can avoid the chips winding on the buffing motors.




Heat Lamp takes the chill out the board to pre heat the board so glue does not set too quickly.



Flat Scraping  
Remove the extra glue which may be left on the panel top and bottom.



Fine Trimming & Scraping Unit  
Two motors traveling on linear guides for end trimming.




Hinge Kit Protection



End Trimming & reciprocating cloth wheels make clean and high gloss buffing. Spray cleaning agent for perfect polishing.




Gravity Fed Top Glue Pot  
Teflon Coated (nonstick)  
Easy Cleaning  
Makes colour changes easy  
EVA to PUR Glues



Edge Press by Rollers  
One big precision roller and 3 small to make sure the edge is pressed seamlessly to the workpiece. All rollers have their independent pressure control valve. The latter further ensures that the edge is properly pressed to the workpiece

## KEY FEATURES

### EF463S AUTOMATIC EDGE BANDER



Spray release agent & Pre-milling Unit Equipped with diamond tools for better cut and longer use.  
This device removes the burr or unevenness on the edge of the workpiece, leaving a smooth surface for the edge banding.  
Spray release agent for perfect pre-milling



Corner Rounding/trimming  
With 2 motors, this device works well with various edge thicknesses and invariably result in perfect round corner.

Item	Description	SKU	Quantity
EF463S	-	EF463S	1
Custom Storage System	storageTest1	Custom Storage System	1
DUST COLLECTOR	DustTest1	NORDFAB	1
tradeTest	-	-	2
TradeTest2	-	-	1
EF463S	-	EF463S	1
DUST COLLECTOR	dustTest2	NORDFAB	1
Subtotal			\$155,000.00
GST(10%)			\$15,500.00
<b>Grand Total</b>			<b>\$170,500.00</b>

# EXCITECH®

---

## CNC TECHNOLOGY

### CONTRACT OF SALE

#### DELIVERY

Estimated delivery time is 6 weeks from date of order confirmation or in stock. The machine price is charged on truck, our works Prestons) / your works (Yenorra). Crane charges also, if required will be charged at cost.

#### PAYMENT TERMS

A 30% deposit is required to secure your order, with the balance due prior to delivery.

Bank details as per below:

Bank Name: ANZ

Account Name: Excitech Australia

BSB: 012430

Account: 330834315

#### INSTALLATION AND COMMISSIONING

Commissioning is included. If commissioning is included an Excitech Australia technician will install and setup the machine correctly. Crane hire, scissor lifts, ducting, tooling, services etc. are not included in price. Commissioning does not include electric, pneumatic or dust exhaust connections. Electrical leads and plugs are not supplied with the machine.

#### ADDITIONAL TRAINING

Additional training is not included.

#### PRODUCT WARRANTY

24 months warranty based on the new machine being operated up to eight hours per day. For use in excess of eight hours per day the term is reduced proportionally.

**VALIDITY**

This offer is valid for thirty days.

**Customer / Company**

**Purchasers Signature**

**Sellers Signature**

Test Excitech

-----

